



11 Hours of Battery Life

(Micro-B USB type)



Float'n Flash



**Optional Speaker-**Microphone, HM-213



\*For illustration purpose only

# <u>IC-M25EURO</u>

### **FEATURES**

# Slim, Lightweight, **High Performance**

The IC-M25EURO has the slimmest (depth: 30.5mm) and lightest (220g) body as a floating marine transceiver\*. It also delivers uncompromised performance that will exceed expectations.

\*As of July, 2015, researched by Icom.

# Large LCD, **Simple User Interface**

The IC-M25EURO's LCD is 30% larger than its predecessor, the IC-M23 and shows clearly large channel number and status icons. The buttons on the front panel are well laid out and provide simple and straightforward operation.

# **USB Charging (Micro-B USB type)**

A standard USB connector (Micro-B type) is used for charging the IC-M25EURO. Cigarette lighter cables or mobile batteries for charging smartphones or other devices can be used with the IC-M25EURO\*.

\* The IC-M25EURO accepts 5V/1A (Max.) input. Use of third-party products is not guaranteed.

### Float'n Flash

The IC-M25EURO floats and lets you know where it is with the flashing red LED light and LCD/key backlight.

# 11 Hours of Battery Life

The built-in 1500mAh lithium-ion battery allows 11 hours (approx.) of long operation\*.

\* Typical operation with Tx (Hi): Rx: standby=5:5:90

# Optional Speaker-Microphone, HM-213

The optional waterproof speaker-microphone, HM-213, provides commercial grade convenience while mounting the radio around the waist. The radio floats even when the HM-213 is attached.

# 550mW Audio Output

The IC-M25EURO provides a powerful 550mW (typical) audio output and received voice can be heard loud and clear.

### Other Features

- IPX7 waterproof construction (1m depth of water for 30 minutes)
- · 4-step battery life indicator
- Dual/Tri-watch functions\*
- Instant access to Ch 16 or programmable call channel
- Favorite channel function
- · Monitor function opens noise squelch
- Auto scan function\*
- · LCD auto backlighting
- AquaQuake<sup>™</sup> draining function
- \* Not available in the HOL version.

### **SPECIFICATIONS**

Squelch sensitivity —6dBµ emf typ. (at threshold) Adjacent channel selectivity 70dB Spurious response 70dB		
Rx 156.000–163.425MHz 156.000–161.600MHz 156.000–161.600MHz 156.000–163.425MHz 156.000–163.425MHz 156.000–163.425MHz 156.000–163.425MHz 156.000–163.425MHz 1NT, USA*, ATIS* channels 1NT, USA*, ATIS* channels 1NT, USA*, ATIS* channels 1Depending on version 16K0G3E (FM)  Power supply voltage 3.7V DC nominal 2.3A 2.3A 2.3A 2.3A 2.3A 2.3A 2.3A 2.3A	GENERAL	
HOL version Tx Rx 156.000–161.600MHz 156.000–163.425MHz  Usable channel groups INT, USA*, ATIS* channels *Depending on version 16K0G3E (FM)  Power supply voltage 3.7V DC nominal  Current drain (at 3.7V DC) Tx 2.3A (Internal SP/External SP) 300mA/200mA (Max. audio)  Operating temperature range -15°C to +55°C  Antenna impedance 50  Dimensions (WxHxD) (projections not included)  Weight (approximately) 220g (With FA-SC59V and MB-133)  TRANSMITTER  Output power 5W (approx.)/1W/0.5W* *For only FRG version  Max. frequency deviation ±5.0kHz  Frequency stability ±1.5kHz  Spurious emissions 0.25µW  Adjacent channel power 70dB  Receiver Sensitivity -6dBµ emf typ. (at 20dB SINAD Spurious response 70dB  Spurious response 70dB  Spurious response	Frequency range Tx	156.000-161.450MHz
Rx 156.000–163.425MHz  Usable channel groups INT, USA*, ATIS* channels * Depending on version  Type of emission 16K0G3E (FM) Power supply voltage 3.7V DC nominal  Current drain (at 3.7V DC) Tx 2.3A Rx (Internal SP/External SP) 300mA/200mA (Max. audio)  Operating temperature range -15°C to +55°C  Antenna impedance 50  Dimensions (WxHxD) (projections not included)  Weight (approximately) 220g (With FA-SC59V and MB-133)  TRANSMITTER  Output power 5W (approx.)/1W/0.5W* * For only FRG version  Max. frequency deviation ±5.0kHz Frequency stability ±1.5kHz  Spurious emissions 0.25µW  Adjacent channel power 70dB  Residual modulation 40dB  RECEIVER  Sensitivity -6dBµ emf typ. (at 20dB SINAD Spurious response 70dB  Spurious response 70dB	1 1/1	
Usable channel groups  INT, USA*, ATIS* channels * Depending on version  Type of emission  Power supply voltage  Current drain (at 3.7V DC)  Tx  Rx (Internal SP/External SP)  Operating temperature range  Antenna impedance  Dimensions (WxHxD) (projections not included)  Weight (approximately)  TRANSMITTER  Output power  Max. frequency deviation  Frequency stability  4.15kHz  Spurious emissions  0.25µW  Adjacent channel power  Residual modulation  RECEIVER  Sensitivity  -6dBµ emf typ. (at 20dB SINAD)  Adjacent channel selectivity  Adjacent channel selectivity  Spurious response  INT, USA*, ATIS* channels  * Depending on version  18K0G3E (FM)  2.3A  2.3A  7.00 (Max. audio)  66.6×134.2×30.5mm  56.6×134.2×30.5mm  56.6×134.2×30.5mm  57.0 (With FA-SC59V and MB-133)  Fransmitter  5W (approx.)/1W/0.5W*  * For only FRG version  4.5.0kHz  5Purious emissions  0.25µW  Adjacent channel power  70dB  Residual modulation  40dB  Receiver  Sensitivity  -6dBµ emf typ. (at 20dB SINAD)  Adjacent channel selectivity  70dB  Spurious response	1102 10101011 17	
Type of emission 16K0G3E (FM) Power supply voltage 3.7V DC nominal Current drain (at 3.7V DC) Tx 2.3A Rx (Internal SP/External SP) 300mA/200mA (Max. audio) Operating temperature range -15°C to +55°C Antenna impedance 50 Dimensions (WxHxD) (projections not included) Weight (approximately) 220g (With FA-SC59V and MB-133)  TRANSMITTER Output power 5W (approx.)/1W/0.5W** For only FRG version Max. frequency deviation ±5.0kHz Frequency stability ±1.5kHz Spurious emissions 0.25µW Adjacent channel power 70dB Residual modulation 40dB  RECEIVER Sensitivity -6dBµ emf typ. (at 20dB SINAD) Squelch sensitivity -6dBµ emf typ. (at threshold) Adjacent channel selectivity 70dB Spurious response 70dB	HX	
Type of emission 16K0G3E (FM)  Power supply voltage 3.7V DC nominal  Current drain (at 3.7V DC) Tx Rx (Internal SP/External SP) 300mA/200mA (Max. audio)  Operating temperature range -15°C to +55°C  Antenna impedance 50  Dimensions (WxHxD) (projections not included)  Weight (approximately) 220g (With FA-SC59V and MB-133)  TRANSMITTER  Output power 5W (approx.)/1W/0.5W** For only FRG version  Max. frequency deviation ±5.0kHz  Frequency stability ±1.5kHz  Spurious emissions 0.25µW  Adjacent channel power 70dB  Residual modulation 40dB  RECEIVER  Sensitivity -6dBµ emf typ. (at 20dB SINAD)  Squelch sensitivity -6dBµ emf typ. (at threshold)  Adjacent channel selectivity 70dB  Spurious response 70dB	Usable channel groups	
Power supply voltage  Current drain (at 3.7V DC) Tx	Type of emission	. 0
Tx Rx (Internal SP/External SP) 300mA/200mA (Max. audio) Operating temperature range Antenna impedance 50 Dimensions (WxHxD) (projections not included) Weight (approximately)  TRANSMITTER  Output power  Max. frequency deviation Frequency stability Spurious emissions 40dB  RECEIVER Sensitivity Sensitivity Sensitivity Sensitivity Spurious response  Adjacent channel selectivity Adjacent channel selectivity Spurious response  70dB  Spurious response 70dB  Spurious response 70dB	Power supply voltage	
Rx (Internal SP/External SP) 300mA/200mA (Max. audio)  Operating temperature range -15°C to +55°C  Antenna impedance 50  Dimensions (WxHxD) (projections not included)  Weight (approximately) 220g (With FA-SC59V and MB-133)  TRANSMITTER  Output power 5W (approx.)/1W/0.5W** For only FRG version  Max. frequency deviation ±5.0kHz  Frequency stability ±1.5kHz  Spurious emissions 0.25µW  Adjacent channel power 70dB  Residual modulation 40dB  RECEIVER  Sensitivity -6dBµ emf typ. (at 20dB SINAD)  Squelch sensitivity -6dBµ emf typ. (at threshold)  Adjacent channel selectivity 70dB  Spurious response 70dB	Current drain (at 3.7V DC)	
Operating temperature range Antenna impedance  Dimensions (WxHxD) (projections not included)  Weight (approximately)  TRANSMITTER  Output power  SW (approx.)/1W/0.5W* For only FRG version  Max. frequency deviation Frequency stability Frequency stability  Spurious emissions  0.25µW  Adjacent channel power  Sensitivity  GedBµ emf typ. (at 20dB SINAD  Recelver  Squelch sensitivity  Adjacent channel selectivity  Adjacent channel selectivity  Adjacent channel selectivity  Spurious response  70dB	Tx	2.3A
Antenna impedance  Dimensions (WxHxD) (projections not included)  Weight (approximately)  TRANSMITTER  Output power  Max. frequency deviation Frequency stability Spurious emissions  Adjacent channel power  Sensitivity  Guelch sensitivity  Adjacent channel selectivity	Rx (Internal SP/External SP)	300mA/200mA (Max. audio)
Dimensions (WxHxD) (projections not included)  Weight (approximately)  TRANSMITTER  Output power  Max. frequency deviation Frequency stability  \$\frac{\pmathbb{\text{5}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}{\pmathbb{\text{5}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}  Max. frequency deviation  \$\frac{\pmathbb{\text{5}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}{\pmathbb{\text{5}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}  Max. frequency deviation  \$\frac{\pmathbb{\text{5}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}{\pmathbb{\text{5}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}  Max. frequency deviation  \$\frac{\pmathbb{\text{5}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}{\pmathbb{\text{5}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}  Max. frequency deviation  \$\frac{\pmathbb{\text{5}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}{\pmathbb{\text{5}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}  Max. frequency deviation  \$\frac{\pmathbb{\text{5}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}{\pmathbb{\text{5}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}  Max. frequency deviation  \$\frac{\pmathbb{\pmathbb{\text{5}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}{\pmathbb{\text{5}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}  Max. frequency deviation  \$\frac{\pmathbb{\pmathbb{\text{5}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}{\pmathbb{\text{6}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}  Max. frequency deviation  \$\frac{\pmathbb{\pmathbb{\text{5}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}{\pmathbb{\text{6}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}  Max. frequency deviation  \$\frac{\pmathbb{\pmathbb{\text{6}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}{\pmathbb{\text{6}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}  Max. frequency deviation  \$\frac{\pmathbb{\pmathbb{\text{6}}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}{\pmathbb{\text{6}{\pmathbb{\text{6}}} (Mith FA-SC59V and MB-133)}  Max. frequency deviation  \$\pm	Operating temperature range	-15°C to +55°C
tions not included)  Weight (approximately)  TRANSMITTER  Output power  Max. frequency deviation Frequency stability  Spurious emissions  Adjacent channel power  Sensitivity  Galbe emf typ. (at 20dB SINAD Adjacent channel selectivity  Adjacent channel selectivity  Adjacent channel selectivity  Adjacent channel selectivity  Squelch sensitivity  Adjacent channel selectivity	Antenna impedance	50
Weight (approximately)  TRANSMITTER  Output power  Max. frequency deviation Frequency stability Frequency stability  Adjacent channel power  Sensitivity  -6dBµ emf typ. (at 20dB SINAD)  Adjacent channel selectivity	, , , ,	56.6×134.2×30.5mm
TRANSMITTER  Output power  Max. frequency deviation Frequency stability Frequency stability Adjacent channel power  Residual modulation  Residual modulation  Residual modulation  Residual modulation  Residual modulation  Adjacent channel power  FodBµ emf typ. (at 20dB SINAD)  Squelch sensitivity  Adjacent channel selectivity  Adjacent channel selectivity  Adjacent channel selectivity  FodBµ emf typ. (at threshold)  Adjacent channel selectivity  FodBµ emf typ. (at mreshold)  Adjacent channel selectivity  FodBµ emf typ. (at mreshold)	tions not included)	000
Output power 5W (approx.)/1W/0.5W* * For only FRG version  Max. frequency deviation ±5.0kHz Frequency stability ±1.5kHz Spurious emissions 0.25µW  Adjacent channel power 70dB  RECEIVER  Sensitivity -6dBµ emf typ. (at 20dB SINAD Squelch sensitivity -6dBµ emf typ. (at threshold)  Adjacent channel selectivity Spurious response 70dB	Weight (approximately)	
Wax. frequency deviation ±5.0kHz Frequency stability ±1.5kHz Spurious emissions 0.25μW Adjacent channel power 70dB RECEIVER Sensitivity -6dBμ emf typ. (at 20dB SINAD Squelch sensitivity -6dBμ emf typ. (at threshold) Adjacent channel selectivity 70dB Spurious response 70dB	TRANSMITTER	
Max. frequency deviation ±5.0kHz Frequency stability ±1.5kHz Spurious emissions 0.25µW Adjacent channel power 70dB Residual modulation 40dB  RECEIVER Sensitivity -6dBµ emf typ. (at 20dB SINAD 50 cleans of the control	0	5W (approx.)/1W/0.5W*
Frequency stability ±1.5kHz  Spurious emissions 0.25µW  Adjacent channel power 70dB  Residual modulation 40dB  RECEIVER  Sensitivity -6dBµ emf typ. (at 20dB SINAD)  Squelch sensitivity -6dBµ emf typ. (at threshold)  Adjacent channel selectivity 70dB  Spurious response 70dB	Output power	* For only FRG version
Spurious emissions Adjacent channel power Residual modulation 40dB RECEIVER Sensitivity -6dBµ emf typ. (at 20dB SINAD Guelch sensitivity -6dBµ emf typ. (at threshold) Adjacent channel selectivity Spurious response 70dB	Max. frequency deviation	±5.0kHz
Adjacent channel power Residual modulation 40dB  RECEIVER Sensitivity -6dBµ emf typ. (at 20dB SINAD Quelch sensitivity -6dBµ emf typ. (at threshold)  Adjacent channel selectivity 70dB  Spurious response 70dB	Frequency stability	±1.5kHz
Residual modulation 40dB RECEIVER Sensitivity -6dBµ emf typ. (at 20dB SINAD quelch sensitivity -6dBµ emf typ. (at threshold) Adjacent channel selectivity 70dB Spurious response 70dB	Spurious emissions	0.25µW
RECEIVER Sensitivity -6dBµ emf typ. (at 20dB SINAD Squelch sensitivity -6dBµ emf typ. (at threshold) Adjacent channel selectivity Spurious response 70dB	Adjacent channel power	70dB
Sensitivity —6dBµ emf typ. (at 20dB SINAD Squelch sensitivity —6dBµ emf typ. (at threshold) Adjacent channel selectivity 70dB Spurious response 70dB	Residual modulation	40dB
Squelch sensitivity —6dBµ emf typ. (at threshold) Adjacent channel selectivity 70dB Spurious response 70dB	RECEIVER	
Adjacent channel selectivity 70dB Spurious response 70dB	Sensitivity	-6dBµ emf typ. (at 20dB SINAD)
Spurious response 70dB	Squelch sensitivity	-6dBµ emf typ. (at threshold)
	Adjacent channel selectivity	70dB
1.1 1.1 1.1	Spurious response	70dB
Intermodulation 68dB	Intermodulation	68dB
Audio output power Internal SP 550mW typ. (12 load, at 1 kHz)	Audio output power Internal SP	550mW typ. (12 load, at 1 kHz)
(at 10% distortion) External SP 200mW (4 load)		200mW (4 load)

Measurements made in accordance with EN301-178-2. All stated specifications are subject to change without notice or obligation

### Applicable IP Rating

Ingress Protection Standard	
Water	IPX7 (Waterproof protection)

**OPTIONS** Some options may not be available in some countries. Please ask your dealer for details.













The "3D GENUINE Icom label" is attached to the rear panel Check the Icom website for details: http://www.icom.co.jp/world/genuine-info

Icom, Icom Inc. and Icom Iogo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. AQUAQUAKE is a trademark of Icom Incorporated. All other products or brands are registered trademarks or trademarks of their respective holders.

ICOM Inc. 1-1-32, Kami-minami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302

Fax: +81 (06) 6793 0013

www.icom.co.jp/world

Count on us!

# Icom America Inc.

12421 Willows Road NE, Kirkland, WA 98034, U.S.A. Phone: +1 (425) 454-8155 Fax: +1 (425) 454-1509 E-mail: sales@icomamerica.com URL: http://www.icomamerica.com

# Icom Canada

Glenwood Centre #150-6165 Highway 17A, Delta, B.C., V4K 5B8, Canada Phone: +1 (604) 952-4266 Fax: +1 (604) 952-0090 E-mail: info@icomcanada.com URL: http://www.icomcanada.com

# Icom Brazil

Rua Itororó, 444 Padre Eustáquio Belo Horizonte MG, CEP: 30720-450, Brazil Phone: +55 (31) 3582 8847 Fax: +55 (31) 3582 8987 E-mail: sales@icombrazil.com

# Icom (Europe) GmbH

Communication Equipment Auf der Krautweide 24 65812 Bad Soden am Taunus, Germany Phone: +49 (6196) 76685-0 Fax: +49 (6196) 76685-50 -mail: info@icomeurope.cor URL: http://www.icomeurope.com

### Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer" Bajos A 08174, Sant Cugat del Valles, Barcelona, Spain Phone: +34 (93) 590 26 70 Fax: +34 (93) 589 04 46 E-mail: icom@icomspain.com URL: http://www.icomspain.com

# Icom (UK) Ltd.

Blacksole House, Altira Park, Herne Bay, Kent, CT6 6GZ, U.K. Phone: +44 (0) 1227 741741 Fax: +44 (0) 1227 741742 E-mail: info@icomuk.co.uk URL: http://www.icomuk.co.uk

# Icom France s.a.s.

Zac de la Plaine, 1 Rue Brindejonc des Moulinais, BP 45804, 31505 Toulouse Cedex 5, France Phone: +33 (5) 61 36 03 03 Fax: +33 (5) 61 36 03 00 E-mail: icom@icom-france.com URL: http://www.icom-france.com

### Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Road, Clayton, VIC 3168 Australia Phone: +61 (03) 9549 7500 Fax: +61 (03) 9549 7505 E-mail: sales@icom.net.au URL: http://www.icom.net.au

# Icom New Zealand

39C Rennie Drive, Airport Oaks, Auckland, New Zealand Phone: +64 (09) 274 4062 Fax: +64 (09) 274 4708 E-mail: inquiries@icom.co.nz URL: http://www.icom.co.nz

# Asia Icom Inc.

Fax: +886 (02) 2559 1874 E-mail: sales @ asia-icom.com URL: http://www.asia-icom.com



Naše kontaktné údaje:

SOUND DESIGN S.C.O. Pribišova 19/A 841 05 Bratislava

Telefón: +421 2 65 45 65 45 Mobil +421 918 246 789 Email: hamtech@hamtech.sk Web: www.hamtech.sk

